

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

THIS PAGE BLANK (USPTO)

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/38, 7/22, H04B 7/26		A1	(11) International Publication Number: WO 99/35870
			(43) International Publication Date: 15 July 1999 (15.07.99)
(21) International Application Number: PCT/FI99/00003		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 4 January 1999 (04.01.99)			
(30) Priority Data: 980016 5 January 1998 (05.01.98) FI			
(71) Applicant (for all designated States except US): NOKIA TELECOMMUNICATIONS OY [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).			
(72) Inventor; and (75) Inventor/Applicant (for US only): FRIMAN, Leif [FI/FI]; Satakunnanpolku 34, FIN-04400 Järvenpää (FI).			
(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).		<p>Published</p> <p><i>With international search report.</i></p> <p><i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p> <p><i>In English translation (filed in Finnish).</i></p>	

(54) Title: METHOD FOR ALLOCATING CHANNELS



(57) Abstract

The present invention relates to a mobile communication system comprising a rate adaptation unit (TC) which communicates with a base station system via first data transmission channels (Ater1 - Ater4) and with a mobile services switching centre (MSC) via second data transmission channels (A1 - A4). To enable available data transmission capacity to be utilized as flexibly as possible, the base station system comprises: allocation means (7) which keep a record of the first data transmission channels (Ater1 - Ater4) and which are responsive to a message sent by the mobile services switching centre (MSC) for allocating one or more free first data transmission channels (Ater2, Ater4) for the call, and transmission means (8) which are arranged to send the mobile services switching centre (MSC) a message which indicates which second data transmission channel (A2) the rate adaptation unit (TC) selects for the call when the allocation means (7) have allocated one or more first data transmission channels (Ater2, Ater4) for the call.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD FOR ALLOCATING CHANNELS

The present invention relates to a method for allocating and selecting data transmission channels for use between a base station system and a mobile services switching centre in connection with call establishment in a mobile communication system in which a rate adaptation unit is arranged on a data transmission connection between the mobile services switching centre and the base station system, the rate adaptation unit communicating with the base station system via first data transmission channels and with the mobile services switching centre via second data transmission channels. The invention further relates to a mobile communication system comprising a mobile services switching centre, a base station system, and a rate adaptation unit which communicates with the base station system via first data transmission channels and with the mobile services switching centre via second data transmission channels, and which comprises means for transmitting telecommunication signals associated with a given call between the mobile services switching centre and the base station system.

The present invention relates to call establishment, and particularly to establishing a data transmission connection between a base station system and a mobile services switching centre particularly in a digital mobile communication system in which a rate adaptation unit is arranged between the mobile services switching centre and the base station system.

In the present application, the concept "base station system" refers to the totality formed by base stations and their control means, i.e. a base station controller. In the present application, the concepts "call" and "call establishment" refer both to common speech calls and to other telecommunication connections transmitted via a mobile communication network, such as data calls and HSCSD (High Speed Circuit Switched Data) data calls.

The frequency spectrum required by a digital mobile communication system, such as a GSM (Global System for Mobile communications) system, for instance, is dependent on the transfer rate used on a radio path. The higher the transfer rate used on the radio path, the broader the spectrum needed. Consequently, speech encoding of a fixed PSTN/ISDN (Public Switched Telephone Network/Integrated Services Digital Network) by which digital encoded data is transmitted 64 kbit/s per each traffic channel, is not usually suitable for use on the radio path. Hence, instead of the speech en-

coding of the fixed network, RPE-LTP (Regular Pulse Excitation - Long Term Prediction) speech encoding is used on a radio path in the GSM system, for example.

It is thus necessary to provide a rate adaptation unit (transcoder) between a base station system and a mobile services switching centre for adapting, for instance, different data transfer rates to each other. In other words, for instance in the GSM system, transcoder interfaces are 64 kbits/s towards the mobile services switching centre and 8 or 16 kbit/s towards the base station system.

In connection with a common full rate call of the GSM system, the mobile services switching centre allocates for a call an "Ater line" (16 kbit/s) between the base station system and the transcoder, i.e. a first data transmission channel, and an A interface line (64 kbit/s) between the transcoder and the mobile services switching centre, i.e. a second data transmission channel. In connection with common calls, one Ater line is thus allocated for one A interface line.

The need to produce quicker data transmission connections has led to the fact that the data transfer capacity of a single Ater line between a base station system and a rate adaptation unit is not sufficient. Additional capacity can be provided for instance in connection with an HSCSD data call in such a manner that several Ater lines are allocated for a call, and the Ater lines are combined by utilizing multiplexing and demultiplexing performed at the rate adaptation unit with one A interface line whose data transfer capacity for instance in the GSM system corresponds to the capacity of four Ater lines. The problem then presented is, however, that in a solution of this kind the mobile services switching centre does not always know which Ater lines are already in use, since it only has information on the A interface lines in use. Consequently, it is possible that the mobile services switching centre makes an allocation which leads to a situation in which two calls try to utilize the same Ater line simultaneously.

An object of the present invention is to solve the problem described above by providing a solution for allocating data transmission channels between a base station system and a mobile services switching centre so as to enable the data transfer capacity available to be entirely utilized as flexibly as possible, which solution enables allocation of a single data transmission channel for two calls simultaneously to be avoided. This object can be achieved by

the method of the invention, characterized in that the method comprises steps of: storing selection information in the base station system and in the rate adaptation unit on which second data transmission channel the rate adaptation unit should allocate for a call for which a given first data transmission channel or channels are allocated, receiving a message which describes the type of a call to be established from the mobile services switching centre, allocating a number of free first data transmission channels required by the call type, determining by means of the selection information which second data transmission channel the rate adaptation unit selects for use, and transmitting information to the mobile services switching centre about the second data transmission channel the rate adaptation unit will select for use.

The invention further relates to a mobile communication system in which the method of the invention can be utilized. The mobile communication system of the invention is characterized in that the base station system comprises: allocation means which keep a record of the first data transmission channels and which are responsive to a message sent by the mobile services switching centre in connection with call establishment for allocating for said call one or more free first data transmission channels required by the call type of the call to be established, and transmission means which are arranged to send the mobile services switching centre on the basis of information stored in the base station system a message which indicates to the mobile services switching centre which second data transmission channel the rate adaptation unit will select for the call when the allocation means have allocated one or more first data transmission channels for the call.

The invention is based on realizing that allocating and managing data transmission channels between a base station and a mobile services switching centre becomes considerably easier and more flexible when channel allocations are carried out by the base station system. In practice, allocation is performed by a base station controller which is aware of those Ater lines which are free at a given moment. Since information is also stored in the base station controller on which A interface line, i.e. second data transmission channel, a rate adaptation unit selects for the Ater lines selected for use, the base station controller is able to transmit the information on the A interface line to be allocated for the call to the mobile services switching centre. Consequently, it is sufficient that the mobile services switching centre informs the base station controller of the type of the call to be established in connection with call estab-

lishment. On the basis of the call type indicated to the base station controller, it is able to infer the number of Ater lines needed and to allocate the necessary free Ater lines, and furthermore, to send a message to the mobile services switching centre to indicate the A interface line via which telecommunication signals associated with the call are transmitted between the rate adaptation unit and the mobile services switching centre.

Hence, the most significant advantages afforded by the solution of the invention are that available data transmission channels can be managed in a simple and flexible manner, that first data transmission channels can be utilized as efficiently as possible, and that second data transmission channels can be successfully managed in all situations independently of the type of a call to be established.

The preferred embodiments of the mobile communication system of the invention are disclosed in the attached independent claims 3 to 5.

The invention will be described in closer detail in the following by way of example with reference to the accompanying drawings, in which

Figure 1 shows a block diagram of a first embodiment of a mobile communication system of the invention,

Figures 2 and 3 illustrate data transmission connections 2 and 3 of Figure 1, and

Figure 4 shows a flow diagram of a first embodiment of the method in accordance with the invention.

Figure 1 shows a block diagram of a first embodiment of a mobile communication system of the invention. The mobile communication system shown in Figure 1 can be a GSM system, for example.

A mobile station MS of Figure 1 communicates with a base station BTS1 which belongs to a base station system 1 via a radio path over a radio interface AIR. From the base station BTS1, telecommunication signals of the mobile station MS which are associated with a call are transmitted through a base station controller BSC to a rate adaptation unit TC via a data transmission connection 2. The rate adaptation unit TC, in turn, communicates with a mobile services switching centre MSC via a data transmission connection 3, whereby the signals of the mobile station MS associated with the call can be transmitted from the mobile station all the way to the mobile services switching centre.

The data transmission connections 2 and 3 consist of circuit switched PCM (Pulse Code Modulation) connections from which a timeslot or part of a timeslot has been allocated for each call. The data transmission connections 2 and 3 are described in closer detail in connection with Figures 2 and 3.

5 In accordance with the invention, the base station controller BSC which belongs to the base station system 1 is responsible for the allocation of telecommunication channels required for a call to be established from the data transmission connections 2 and 3. This is performed in such a manner that in connection with call establishment, the mobile services switching centre MSC
10 sends the base station controller BSC a message S1 by which it indicates the type of the call to be established. The message is sent for instance in an AS-SIGNMENT message which the mobile services switching centre would send in any case to the base station controller in connection with call establishment.
15 The base station controller BSC keeps a record of the free channels of the data transmission connection 2, so it can allocate a number of channels required by the call type in question from the data transmission connection 2. The base station controller also knows which channel the rate adaptation unit TC selects from the data transmission connection between it and the mobile
20 services switching centre, in which case it can indicate the channel of the data transmission connection 3 on which the telecommunication signals associated with the call will be transmitted to the mobile services switching centre by a message S2 sent to the mobile services switching centre.

Figures 2 and 3 illustrate the data transmission connections 2 and 3
25 of Figure 1. Figure 3 illustrates a frame structure used on the circuit switched PCM connections 2 and 3. A frame consists of 32 timeslots TS0...TS31, each having a 64 kbit/s data transmission capacity.

Since telecommunication signals are transmitted from the base station controller BSC at a rate of 16 kbit/s in connection with a full rate call of a
30 GSM system mobile station, the 64 kbit/s timeslots between the rate adaptation unit and the base station controller BCS are divided into sub-timeslots called Ater lines. One timeslot, illustrated in connection with a timeslot TS1, comprises four Ater1...Ater4 Ater lines, i.e. first telecommunication channels.

The telecommunication signals associated with the full rate call are
35 transmitted from the rate adaptation unit TC to the mobile services switching

centre MSC by A interface lines A1 to A4 whose data transfer capacity is 64 kbit/s. One A interface line thus occupies one PCM timeslot entirely.

In accordance with the invention, the same selection information is stored in a memory 5 of the base station controller and in a memory 6 of the rate adaptation unit, and on the basis of the selection information is determined via which A interface line telecommunication signals associated with a given call should be forwarded to the mobile services switching centre when given Ater lines have been allocated for the call. In other words, the selection information can consist of a table indicating that, for instance

10	When selected	Should be selected
	Ater1	A1
	Ater2	A2
	Ater2 & Ater4	A2
15	Ater3 & Ater4	A3
	Ater 1-3	A1
	Ater 1 & 2 & 4	A1

It is to be noted that the table shown above by way of example is not complete; in practice, the table can comprise an A interface line to be selected for all possible Ater line combinations. It is essential that the information stored in the base station controller and the rate adaptation unit is identical, in which case it is sufficient that an allocation unit 7 of the base station controller allocates the Ater lines, whereupon a transmitter 8 can send the mobile services switching centre a message S2 which indicates the A interface line by which the call is transmitted.

When the allocation unit 7 has allocated the Ater lines for instance for an HSCSD call requiring two Ater lines, it informs the rate adaptation unit TC of the allocation. This is performed in such a manner that the allocation unit 7 transmits a given bit pattern on the allocated Ater lines. The allocation unit 7 can signal a free Ater line to the rate adaptation unit for instance by transmitting a bit pattern 01B on the Ater line in question. The allocation unit 7 can signal a coming two-Ater-line call to the rate adaptation unit for instance by transmitting a bit pattern 10B on the Ater lines in question. The allocation unit 7 can signal a coming three-Ater-line call to the rate adaptation unit for instance by transmitting a bit pattern 11B on the Ater lines in question, etc.

Alternatively, the allocation unit 7 can, for instance, signal a coming three-Ater-line call to the rate adaptation unit by transmitting a predetermined bit sequence only on one of the Ater lines which will be used. The bit sequence in question thus indicates the other Ater lines which will be used to the rate adaptation unit.

An identification unit 9 of the rate adaptation unit TC monitors continuously the Ater lines, thus being able to identify bit patterns transmitted on the lines. Hence, when it for instance detects the bit pattern 10B on lines Ater2 and Ater4, it informs a control unit 10 of this. The control unit then finds out, on the basis of the selection information in the memory 6, on which A interface line the two-Ater-line call in question should be forwarded. According to the above table, the correct A interface line is A2. The control unit 10 thus activates the rate adaptation unit to start forwarding the telecommunication signals received from the Ater lines Ater2 and Ater 4 via the A interface line A2 (after necessary rate adaptation procedures known per se). Signals are thus transmitted until the identification unit detects the bit pattern 01B on the Ater lines Ater2 and Ater4 (free line = call terminated), whereby the rate adaptation unit TC stops transmitting signals.

Figure 4 shows a flow diagram of a first embodiment of the method in accordance with the invention. In block A, identical selection information is stored in a base station controller BSC and a rate adaptation unit, the selection-information-indicating-which-A-interface-line-should-be-selected-for-a-call for which given Ater lines are allocated.

In block B, a message which describes the type of the call is received from a mobile services switching centre in connection with call establishment. The mobile services switching centre can send this message in connection with an ASSIGNMENT message, for example.

In block C, a number of free Ater lines required by the call type is allocated. In other words, if the call is a two-time-slot HSCSD call, two Ater lines are allocated. Next, the same given bit pattern is transmitted via the allocated Ater lines, the bit pattern indicating to the rate adaptation unit that the Ater lines in question are allocated for the same call. Consequently, the rate adaptation unit is able to find out on which A interface line it should start transmitting the telecommunication signals associated with the call.

In block D, the A interface line to be used is found out on the basis of the selection information and the allocated Ater lines.

In block E, the mobile services switching centre is informed of the A interface line to be used. In this stage, the telecommunication channels between the base station system and the mobile services switching centre which are associated with the call are selected, and the call establishment can be continued in a manner known per se.

It is to be understood that the above description and the accompanying drawings are only intended to illustrate the present invention. It will be obvious to those skilled in the art that the invention can be varied and modified in many ways without departing from the scope and spirit of the invention disclosed in the attached claims.

CLAIMS

1. A method for allocating and selecting data transmission channels for use between a base station system and a mobile services switching centre in connection with call establishment in a mobile communication system in which a rate adaptation unit is arranged on a data transmission connection between the mobile services switching centre and the base station system, the rate adaptation unit communicating with the base station system via first data transmission channels and with the mobile services switching centre via second data transmission channels, **characterized** in that the method comprises steps of:
- storing selection information in the base station system and in the rate adaptation unit on which second data transmission channel the rate adaptation unit should allocate for a call for which a given first data transmission channel or channels are allocated,
- receiving a message which describes the type of a call to be established from the mobile services switching centre,
- allocating a number of free first data transmission channels required by the call type,
- determining by means of the selection information which second data transmission channel the rate adaptation unit selects for use, and
- ~~transmitting information to the mobile services switching centre~~ about the second data transmission channel the rate adaptation unit will select for use.
2. A mobile communication system comprising
- a mobile services switching centre (MSC),
- a base station system (1), and
- a rate adaptation unit (TC) which communicates with the base station system (1) via first data transmission channels (Ater1 - Ater4) and with the mobile services switching centre (MSC) via second data transmission channels (A1 - A4), and which comprises means for transmitting telecommunication signals associated with a given call between the mobile services switching centre and the base station system, **characterized** in that the base station system (1) comprises:
- allocation means (7) which keeps a record of first data transmission channels (Ater1 - Ater4) and which are responsive to a message (S1) sent by

the mobile services switching centre (MSC) in connection with call establishment for allocating for said call one or more free first data transmission channels (Ater2, Ater4) required by the call type of the call to be established, and

transmission means (8) which are arranged to send the mobile services switching centre (MSC) on the basis of information stored in the base station system (1) a message (S2) which indicates to the mobile services switching centre which second data transmission channel (A2) the rate adaptation unit (TC) will select for the call when the allocation means (7) have allocated one or more first data transmission channels (Ater2, Ater4) for the call.

3. A mobile communication system as claimed in claim 2, **characterized** in that the rate adaptation unit (TC) comprises:

a memory means (6) in which selection information is stored which indicate the second data transmission channel (A2) the rate adaptation unit (TC) should select for the call for which the base station system (1) has allocated the given first data transmission channels (A2, A4),

identification means (9) which are arranged to monitor the first data transmission channels (Ater1 - Ater4) for identifying the first data transmission channels (Ater2, Ater4) allocated for the given call by the base station system, and

a control unit (10) responsive to the identification means (9), arranged to select one of said second data transmission channels (A2) for the call on the basis of the information stored in the memory means (6) when the identification means (9) have identified the first data transmission channels (Ater2, Ater4) allocated for the call, and which control unit is arranged to activate the rate adaptation unit (TC) to start transmitting telecommunication signals associated with the call between the allocated first data transmission channels (Ater2, Ater4) and the selected second data transmission channel (A2).

4. A mobile communication system as claimed in any one of claims 2 or 3, **characterized** in that the allocation means (7) of the base station system are arranged to inform the rate adaptation unit (TC) of the allocated first data transmission channels (Ater2, Ater4) by transmitting to the rate adaptation unit (TC) a predetermined bit pattern on the allocated first data transmission channels in connection with call establishment.

5. A mobile communication system as claimed in any one of claims 2 to 4, **characterized** in that said mobile communication system is a

GSM system, that the rate adaptation unit consists of a transcoder (TC), and that said allocation means (7) and said transmission means (8) of the base station system (1) are arranged in a base station controller (BSC).

THIS PAGE BLANK (USPTO)




FIG. 1




FIG. 2




FIG. 3

THIS PAGE BLANK (USPTO)

2/2




FIG. 4

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 99/00003

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04Q 7/38, H04Q 7/22, H04B 7/26
According to International Patent Classification (IPC) or to both national classification and IPC.

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04B, H04Q, H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPIL, EDOC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 19713164 A1 (KABUSHIKI KAISHA TOSHIBA, KAWASAKI, KANAGAWA, JP), 6 November 1997 (06.11.97), see the whole document	1-5
X	US 5644570 A (PETER SKALSKY), 1 July 1997 (01.07.97), abstract, see the whole document	1-5
X	WO 9815152 A (LM ERICSSON TELEFON AB), 9-April-1998 (09.04.98), see the whole document	1-5

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 June 1999

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Date of mailing of the international search report

15 -06- 1999

Authorized officer

Malin Gullstrand/mj

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

03/05/99

International application No.

PCT/FI 99/00003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19713164 A1	06/11/97	AU 683608 A	13/11/97
		CN 1166763 A	03/12/97
		JP 9270763 A	14/10/97
<hr/>			
US 5644570 A	01/07/97	AT 154865 T	15/07/97
		CH 681938 A	15/06/93
		DE 59208645 D	00/00/00
		EP 0539540 A,B	05/05/93
		EP 0765102 A	26/03/97
		JP 6500223 T	06/01/94
		US 5432792 A	11/07/95
		WO 9221216 A	26/11/92
		CH 682868 A	30/11/93
		CH 683218 A	31/01/94
<hr/>			
WO 9815152 A	09/04/98	AU 4478497 A	24/04/98
		SE 507432 C	08/06/98
		SE 9603560 A	31/03/98
<hr/>			